



This pump is a domestic submersible water pump supplied wired and ready to install.

**The pump is characterized by:**

- ☐ Fully automatic operation
- ☐ 240V single phase motor with built-in auto reset thermal overload.
- ☐ 10m power cable
- ☐ Not suitable for construction sites, ponds, fountains or bio-treatment.
- ☐ Flows up to 117 l/m
- ☐ Max head 8m

**Liquid:**

Clean water temperature range: 2-35°C

**Materials:**

Pump body, Impeller, Strainer: ABS  
Shaft Seal: Mechanical seal  
Carbon / Ceramic  
O rings: Nitrile

**Installation:**

Maximum liquid temperature: 35°C  
Discharge connection: 1 1/2" BSPF  
(additional fittings provided in carton)

**Electrical Data:**

Rated voltage: 240V  
Mains frequency: 50Hz  
Rated output: 400W  
Current: 2 amps  
Capacitor: 8µF  
Motor duty: Continuous  
Motor type: Asynchronous, TEFC  
Motor protection: Built-in thermal overload  
Ingress protection: IPX8  
Insulation class: F  
Power cable length: 10m H07RNF  
Gross weight: 5 kg  
Carton dimensions: 220 x 180 x 390mm

**12 MONTHS BIANCO Pumpz Warranty**

Also Available -

BIA-JH400I 1S2, BIA-JH8003S2,  
BIA-JH550BS2

**BIA-JH400S2**

