

SPECIFICATION



GALCON HOSE END IRRIGATION CONTROLLER

Two station battery operated hose end timer suitable for 25mm and 20mm garden taps

FEATURES

Two watering stations from one tap - using ALTVALVE
Easy to install and use
Operated with 9v alkaline battery (not included)
Run times from 1 minute - 12 hours
Four start times per day
Individual day programming
Manual activation at controller
Rain off suspension option
Rain sensor override ready
Low battery indicator
Internal filter installed in controller



SPECIFICATIONS - 9001D TAP TIMER

Power 1 x 9v alkaline battery (not included)
Maximum flow 1200 Lph - *flow rate above 1200lph will blow timer off tap*
Minimum flow 100 Lph - *flow rate below 100lph will prevent timer from closing*
Maximum working pressure 800kPa - *do not install above 800kPa*
Minimum working pressure 100kPa - *do not install below 100kPa*
Supplied with 20mm and 25mm tap adapter
Rain sensor shutdown (yellow wires)

SPECIFICATIONS - ALTVALVE - TWO OUTLET VALVE

Two 20mm male outlets
Maximum flow 1200 Lph - *flow rate above 1200lph will blow timer off tap*
Minimum Flow 100 Lph - *flow rate below 100lph will prevent timer from closing*
Maximum working pressure 800kPa - *do not install above 800kPa*
Minimum working pressure 100kPa - *do not install below 100kPa*



OPERATION - ALTVALVE

Activation of a watering cycle by the 9001D will allow water to flow from one outlet. Subsequent activations by the 9001D will switch the outlet ports. No more than one outlet port open at any time
Example - controller starts at 6:30am one port will open, next controller start time will open the opposite port. The red arrow indicates next open port

CAUTION

Hand tight the two port valve onto 9001D outlet only. To align the two port valve hand rotate anticlockwise with red arrow facing outwards. Using wrench or vice grips may force the two port valve to jump out of outlet thread voiding warranty.

MODELS	CODE
Galcon hose end irrigation controller	9001D
Galcon two way alternating valve for 9001D	ALTVALVE
9 volt alkaline battery	9V-ALK-B
Senninger pressure regulator 275kPa factory set	PRLV40

Specifications Subject to Change Without Notice - Product Drawings / Images are representative only and are subject to change

PERTH

PH: 08 9455 1677
FAX: 08 9455 1680
hrsales@hrproducts.com.au

SYDNEY

PH: 02 9725 5733
FAX: 02 725 5283
infonsw@hrproducts.com.au

MELBOURNE

PH: 03 9457 7500
FAX: 03 9457 7400
infovic@hrproducts.com.au

BRISBANE

PH: 07 3806 0522
FAX: 07 3806 0533
infoqld@hrproducts.com.au

ADELAIDE

PH: 08 8341 0008
FAX: 08 8341 0707
infoasa@hrproducts.com.au