

EZ Flo Plus™ Series

Residential and Light Commercial Valves

VALVES

Proven reliability. Easy to install and service. That's exactly what installers want in a solenoid valve.

Building on Toro's history of Flo Pro® valves, these new control valves provide lower frictional losses, more compact size, reduced spare parts costs and a longer warranty.

As well as the threaded versions we have a slip option for P.V.C. laterals.

Ez-Flo Plus™ series provide exceptional valve and Toro's famous quality.



SPECIFICATIONS

25 mm Electric Models



Mechanical

- Dimensions: Height: 130 mm
Width: 75 mm
Length: 101 mm

Specifying Information

- Flow range: 1 - 114 LPM
- Operating pressure: 70 - 1035 kPa
- Body style: Globe valve with 25 mm FBSP inlet and outlet.
- Solenoid: 24 VAC, 50 Hz
 - Inrush: 0.34 Amps
 - Holding: 0.20 Amps

Options Available

- DC latching solenoid assembly. (E2002-A)

N.B. The maximum pressure for a valve that utilises a E2002-A DC latching solenoid is 830 kPa, and larger sized cable will possibly be needed.

- Slip x Slip ports for PVC lateral installations.

Please refer to the Toro Price List for ordering information on the EZ Flo Plus™ valves.

Features

- Tough, double-beaded Santoprene diaphragm for a longer life and to minimise leaking
- Resilient Buna-N diaphragm seat seal
- Manual internal bleed
- Manual external bleed (flush / commissioning mode)
- Full stainless-steel metering system
- Floating bleed tube allows thermal expansion without effecting performance
- Heavy-duty PVC, glass-filled nylon and stainless steel construction (corrosion and UV-resistant)
- Encapsulated solenoid with captured hex plunger and spring
- Threaded bonnet system with heavy-duty cap ring (no screws) for fast and easy servicing
- Easily serviced without removal from the system
- Extended 3 year warranty

For further information please contact your local irrigation dealer or call Toro on 1300 130 898