



PROJECT \_\_\_\_\_

CATALOG # \_\_\_\_\_

TYPE \_\_\_\_\_



NOTES \_\_\_\_\_

## EX Transformer

The EX transformer provides an economical, low-wattage power and control option for LED lighting projects.

### Quick Facts

- 150 watts
- Single 15-volt output tap
- Compact design
- Powder-coated steel or stainless steel options
- Compatible with most 120 VAC plug-in astronomical timers and photocells



# EX Transformer SPECIFICATIONS

## Output

<b>Power</b>	150 W	150 W
<b>Input Primary</b>	120 V, 60 Hz	230 V, 50/60 Hz
<b>Input Amperage Primary</b>	1.4 A	0.65 A
<b>Output Voltage Secondary</b>	14 VAC	14 VAC
<b>Maximum Open Circuit Volts</b>	15 VAC	15 VAC
<b>Class</b>	2	2

### FX Luminaire

FX Luminaire is an industry-leading manufacturer of landscape and architectural lighting products with a focus on the advancement of LED technology and digital lighting control with zoning, dimming, and color adjustment capabilities. We offer a full spectrum of specification-driven lighting fixtures that can be used to create elegant landscape lighting systems for commercial or residential applications. Our products are available exclusively via our extensive professional distributor network.

### Materials

**304** Stainless steel and Powder coated steel outer box.

### Wiring

Heavy-gauge, grounded, water-resistant power cord with integrally molded plug; 6' (1.8 m) length.

Standard low-voltage lighting wire required (e.g., 12-2, 10-2, etc.) between controller and fixtures. No additional communication wire is required.

### Power

Input: 120 VAC, 60 Hz; Output: 15 VAC.  
e version: Input 230 VAC, 50/60 Hz; Output: 15 VAC.

### Finish

Standard stainless steel finish and matte gray powder coat.

### Weight

15.1 lbs. (6.9 kg)

### Hardware

Two pan-head machined mounting screws with plastic anchors. Mounting brackets attached to transformer box.

### Ambient Operating Temperature

0°F to 140°F (-18°C to 60°C)

### Sustainability

Innovation meets conservation in the design and manufacturing of our products. Where we can, we use recycled materials while maintaining superior functionality. Our LED products provide high-quality light at optimal energy efficiency, lifespan, and durability.

### Installation Requirements

Designed for installation on a vertical surface in the upright position only.

### Warranty

10-year limited warranty.

### Listings

UL-1838  
UL-379 (Pool and Spa)  
IEC 61588-1



# EX Transformer ORDERING INFORMATION

Transformer	Output	Compliance	Finish
<b>EX</b> Transformer	■ 150 150 Watts	■ [default] 120 V (North America)	■ M Matte Gray
		■ e** 230 V (International)	■ SS* Stainless Steel





\*UL 379 - Pool and Spa rated

\*\*Only available in Matte Gray

EXAMPLE TRANSFORMER CONFIGURATION: EX-150-M

EX - 150 - M

## ACCESSORIES: Specify Separately

Item	Code	
■ MECHANICAL TIMER Plug-in	PXTIMER	
■ PX TRANSFORMER SYNCHRONIZER Plug-in, 24 VAC input	PXSYNC	
■ PHOTOCELL Plug-In	EXPC	
■ PHOTOCELL (230V) Plug-In	EXPCE	

© 2019 Hunter Industries Inc. Hunter, FX Luminaire, and all related logos are trademarks of Hunter Industries, registered in the U.S. and other countries.