

## HC LED Path Light DESIGNER PREMIUM




---

PROJECT

---

CATALOG #

---

TYPE

---


NOTES

---

Modeled after our most popular Path Light, the HC is the perfect addition to any pathway. The petite and clean lines of the HC allow for unobtrusive placement, which can therefore enhance your surrounding colors and textures. Inside is Driver-on-Board LED technology that offers energy savings and long lamp life.

### Quick Facts

- Copper/brass construction
- Natural, powder coated, or antiqued copper/brass
- Lumileds® Integrated LEDs
- Compatible with Luxor® technology
- Phase and PWM dimmable
- Input voltage: 10-15V



**Note:** Example model shown has a 12" riser.

HC Path Light - Recommended Spacing  
1 LED

Footcandles (Lux)	12" Riser	18" Riser
0.1 fc (1.1 lx)	6.5' (2.0 m)	8.4' (2.6 m)
0.3 fc (3.2 lx)	5.0' (1.5 m)	6.6' (2.0 m)
0.5 fc (5.4 lx)	4.5' (1.4 m)	6.0' (1.8 m)
0.8 fc (8.6 lx)	4.3' (1.3 m)	5.0' (1.5 m)
1.0 fc (10.8 lx)	4.0' (1.2 m)	4.5' (1.4 m)

0.1 fc (1.1 lx) minimum spacing recommended for residential projects

0.3 fc (3.2 lx) minimum spacing recommended for commercial projects

# HC LED Path Light SPECIFICATIONS

Number of LEDs	1
Halogen Lumen Output Equivalent	51 Watt
Useful LED Life (L70)	50,000 hrs avg
Input Voltage	10 to 15V
VA Total (Use this number to size the transformer)	1.9
Watts Used	2.2
Lumens per Watt (Efficacy)	28
Max Lumens	39
CRI (Ra)	86
CCT	
Amber Filter	2700K
Green Filter	4500K
Blue Filter	5200K

## HC Path Light - Recommended Spacing 1 LED

Footcandles (Lux)	12" Riser	18" Riser
0.1 fc (1.1 lx)	6.5' (2.0 m)	8.4' (2.6 m)
0.3 fc (3.2 lx)	5.0' (1.5 m)	6.6' (2.0 m)
0.5 fc (5.4 lx)	4.5' (1.4 m)	6.0' (1.8 m)
0.8 fc (8.6 lx)	4.3' (1.3 m)	5.0' (1.5 m)
1.0 fc (10.8 lx)	4.0' (1.2 m)	4.5' (1.4 m)

0.1 fc (1.1 lx) minimum spacing recommended for residential projects  
 0.3 fc (3.2 lx) minimum spacing recommended for commercial projects

# HC LED Path Light SPECIFICATIONS

## FX Luminaire

FX Luminaire is an industry-leading manufacturer of landscape and architectural lighting products with a focus on the advancement of LED technology and digital lighting control with zoning, dimming, and color adjustment capabilities. We offer a full spectrum of specification-driven lighting fixtures that can be utilized to create elegant, cutting-edge landscape lighting systems for commercial or residential applications. Our products are available exclusively via our extensive professional distributor network.

## Materials

Machined C360 brass cap and reducer with stainless hardware. Spun C110 copper top/shade and extruded C110 copper riser.

## LED

Integrated module with Cree LEDs. Gold-plated connectors and conformal coated for maximum reliability and corrosion resistance. Proprietary on-board intelligent driver uses firmware-controlled temperature regulation, maximizing LED life. Field upgradeable and replaceable, the LEDs are rated to 50,000 hrs. Maximum drive current: 1 A.

## Threads

Machined brass fitting with ½"-14 (13 mm) NPSM threads.

## Finish

Options of natural copper/brass finish, or antiqued finish with brushed (Antique Bronze) or tumbled (Antique Tumbled) effect. Antique finishes sealed with a clear TGIC powder coat layer. Brass accent pieces (cap and reducer) remain natural (not powder coated) for Bronze, Silver, Black, and Flat White finishes.

## Hardware

Includes 12" (305 mm) ABS slotted installation spike.

## Wiring

18 AWG (1 mm); SPT-1W; 220°F (105°C); 300V; 3' (1.5 m) length with 12" (305 mm)riser.

## Optics

Polycarbonate color temperature adjustment lenses included with fixture: 2,700K (preinstalled), 3,900K (no lens) 4,500K, and 5,200K. Conical reflector maximizes distribution according to riser height. Color temperature lenses field serviceable.

## Power

Input 10-15 VAC/VDC, 50/60Hz. Remote transformer required (specify separately).

## Housing

Machined brass housing with capacity for 1LED integrated LEDs.

## Weight

2.7 lbs (1.2 kg)

## Lens

Frosted polycarbonate lens with high tolerance for thermal expansion, stress, and abuse.

## International Compliance

Compliant per IEC 60598-1 and IEC 60598-2-7 when used with ground mount ("GM-XX") accessory, or alternate mount greater than or equal to IP65.

## Ambient Operating Temperature

0°F to 140°F (-18°C to 60°C)

## Sustainability Installation Requirements

Designed for installation in the downward lighting direction only.

## Control

ZD option utilizes Luxor technology to zone light fixtures in up to 250 groups, and dim each group in 1% increments between 0 and 100%. Select the ZD option for zoning/dimming. Standard fixture is zoneable with Luxor.

## Warranty

## Listings



# HC LED Path Light ORDERING INFORMATION

Fixture	Top Finish	Riser	Luxor Option	Lamp	Riser Height	Finish
<b>HCLEDTA</b>	<b>AB</b> Antique Bronze	<b>P</b> (Petite)	<b>[default]</b> Zone	<b>1 LED</b> 2.0W/2.4VA	<b>12RA</b>	<b>AB</b> Antique Bronze
	<b>AT</b> Antique Tumbled					<b>AT</b> Antique Tumbled
	<b>CU</b> Copper				<b>18RA</b>	<b>CU</b> Copper
	<b>NP</b> Nickel Plate				<b>24RA</b>	<b>NP</b> Nickel Plate
	<b>BZ</b> Bronze Metallic					<b>BZ</b> Bronze Metallic
	<b>DG</b> Desert Granite					<b>DG</b> Desert Granite
	<b>WI</b> Weathered Iron					<b>WI</b> Weathered Iron
	<b>SB</b> Sedona Brown					<b>SB</b> Sedona Brown
	<b>FB</b> Flat Black					<b>FB</b> Black
	<b>FW</b> Flat White					<b>FW</b> Flat White
<b>SV</b> Silver					<b>SV</b> Silver	



EXAMPLE FIXTURE CONFIGURATION: HC-ZD-1LED-12R-CU

\* Ships with Long Slot Spike (250015840000)












## HC Path Light - Recommended Spacing

Footcandles (Lux)	1 LED	
	12" Riser	18" Riser
0.1 fc (1.1 lx)	6.5' (2.0 m)	8.4' (2.6 m)
0.3 fc (3.2 lx)	5.0' (1.5 m)	6.6' (2.0 m)
0.5 fc (5.4 lx)	4.5' (1.4 m)	6.0' (1.8 m)
0.8 fc (8.6 lx)	4.3' (1.3 m)	5.0' (1.5 m)
1.0 fc (10.8 lx)	4.0' (1.2 m)	4.5' (1.4 m)

0.1 fc (1.1 lx) minimum spacing recommended for residential projects



0.3 fc (3.2 lx) minimum spacing recommended for commercial projects

MOUNTING OPTIONS: Specify Separately

Mounts	Catalog No.		Mounts	Catalog No.	
Long Slot Spike	250015840000		Three-Prong Spike	250020020000	
Super Slot Spike	753900		Ground Mount with 1/2" Thread	GM-XX*	
Mini J-Box for 1/2" Thread	MJB-050-XX*		ProAim® Ratcheting Spike	PARS	
Post Mount	PM-XX*		Super J-Box Spike	SJ-XX*	
VersaBox® Mount with 1/2" Thread	VB-050-XX*		Variable Height Riser for Up Lights	VHR-UL	
1.0" (25 mm) Copper Riser for GT Path Light	YY*-R-GT-XX*				

# HC LED Path Light ORDERING INFORMATION

POWER OPTIONS: Specify Separately

Power	Catalog No.	
Plug-in transformer, 6W	MT-6W	
Lighting Fixture Surge Module	SURGE-MOD	

Power	Catalog No.	
Step-Down Transformer, UV (120/277 V to 12 V)	ST-UV	